



Part#	HT-X33460	Application	Toyota 4Runner All
-------	-----------	-------------	--------------------

Gross Load Capacity When Used As A Weight Carrying Hitch: 5000 LBS. Trailer Weight & 500 LBS. Tongue Weight.
Gross Load Capacity When Used As A Weight Distribution Hitch: 6000 LBS. Trailer Weight & 600 LBS. Tongue Weight.
*****DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.*****

* No Drilling Required

PASSENGER SIDE FRAME RAIL

PASSENGER SIDE WELDNUT PLATE

EXISTING WELDNUT

DRIVER SIDE FRAME RAIL

DRIVER SIDE WELDNUT PLATE

EXISTING M12 BOLTS

A

B

C

1

2

FRONT

REAR

Page1 of 2



Hitch Installation Instructions

Part#	HT-X33460	Application	Toyota 4Runner All
Step	Description		
1	Assemble Hitch Body (A) and Mounting Brackets (B, C) with (8) M12X1.75-35mm Hex Bolts, (16) M12 Flat Washers, (8) M12 Hex Flange Nuts. (Hardware in “HW A”). Note: Finger tighten only. Do not fully tighten at this time.		
2	Remove tow hooks from vehicle frame.		
3	Position weld-nut plate inside frame as shown.		
4	Raise hitch into position and align the side brackets with the existing tow hook holes at the end of the frame rails. Reinstall the existing M12 bolts and tow hooks removed in step 2.		
5	Insert M12 bolt and conical tooth washer through rearmost existing hole in hitch. This will thread into weld-nut plate as shown. Hand tighten only at this time.		
6	Insert M12 bolt and conical tooth washer through foremost existing hole in hitch. This will thread into weld-nut plate as shown. Hand tighten only at this time.		
7	Torque all M12 fasteners to 86 lb-ft.		
***Periodically Check The Receiver Hitch To Ensure That All Fasteners *** Are Tight & All Structural Components Are Sound.			

The instructions here are for your reference only. We strongly recommend professional installation for best results. We are not responsible for any damage caused by the installation. Thank you for choosing our product!